## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T30N R29W Montana Principal Meridian G.L.O. notes book 8958 page 166 has an iron post 30" long 22" in diameter, 26" in the ground with a brass cap marked MC Found the brass cap in good condition and 518 517 undisturbed.

T30N R29W 1965

Record: A rotted stump bearing N39½°W, 9 lks., with no legible markings Found: Rotted stump bearing N36°W, 9 lks., with no legible scribe

Record: 31" pine bearing S40°55'E, 61 lks., with some scribe marks visible Found: Bearing tree alive and presently 33" in diameter

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Way '74

No added monumentation

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side for sketch

Surveyor's Seal

MARTIN NT A JOHN C **ERICKSON** 3979 S SURVE VORM

Form 125-3690

correct.

> lames R. Staples Signature of Ground Party Chief

JOHN C. ERICKSON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Olu Signature of Surveyor

3979 S Registration Number

DIAGRAM OF CORNER:

N.

517

T3ON R29W

= Corner recorded on the sheet

Office of Clerk and Recorder, County of ....

assigned page No......, in book No.....

This "corner record" was filed for record on the 28 day of \_\_\_\_\_\_

19...., was noted on the cross-index plat and is

Official 30N

29 W

Cross Index No...... T.....

