

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T30N R30W Montana Principal Meridian G.L.O. notes book 3420 page 32 has limestone 14x10x6 X 9" in the ground with 4 bearing trees. Found no indication of trees or corner. Reset acorner by double proportion method. Double proportioned from the 4 surrounding \(\frac{1}{4} \) corners.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: June 74

DIAGRAM OF CORNER:

Set Corps of Engineers Brass cap and 4 bearing trees. COE brass cap shown on reverse side.

- 1) 36" fir bearing $N84\frac{1}{2}$ °E, 172 lks., marked T30N R30W S4 BT
- 2) 30" tamarack bearing S75% E, 219 lks., marked T30N R30W S9 BT
- 3) 15" fir bearing S21W, 160 lks, marked T30N R30W S8 BT
- 4) 12" fir bearing N66°W 245 lks., marked T30N R30W S5 BT

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side

Form 125-3690

I, _____James R. Staples _____certify that the information shown herein is true and Surveyor's Seal T30N R30W correct. MATA MONTAN Signature of Ground Party Chief JOHN C. ERICKSON certify that I have carefully performed or reviewed the JOHN C. work done on the diagrammed corner as reported on this ERICKSON recordation form and approve the same. 3979 S = Corner recorded on the sheet SURVEYOUR mus Signature of Surveyor 3979

Office of Clerk and Recorder, County of This "corner record" was filed for record on the 28 day of Mor 1957, was noted on the cross-index plat and is assigned page No. 3980 , in book No. T 30N R 30W Mer.

Registration Number

12" FIR MRKD T30N R30W S5 BT 4 BERS CAP ENG INFERS 36" FIR MRKO: T30N R30W 34 BT 5,59 1974 8 30" TAMARACK MRKD: F30N R30W S9 BT 15" FIR, MRKD TOON ROOW SE BT