CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T30N R29W Montana Principal Meridian G.L.O. notes book 8958 page 143 has an iron post 30" long, 21" in manufactory diameter, 26" in the ground with a brass cap marked T30N

R30W R29W

Found the brass cap in good condition.

S13 | S18

Record: 14" fir bearing S26°10'W, 19 lks., marked with an overgrown blaze Found: Bearing tree alive and presently 16" in diameter

Record: 11" larch bearing S80°E, 59 1ks., marked $\frac{1}{2}$ S18 BT Found Bearing tree alive and presently 12" in diameter

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: May 74

No added monumentation

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See sketch on reverse side

Surveyor's Seal

JOHN C.
ERICKSON
3979 S

**CGISTERED
OSURV

James R. Staples

certify that the information shown herein is true and correct.

James

Signature of Ground Party Chief

JOHN C. ERICKSON

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this

recordation form and approve the same.

Signature of Surveyor

3979 5 Registration Number DIAGRAM OF CORNER:

730N R29W
N. 1/4

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoh

This "corner record" was filed for record on the 28 day of Max

..... 19...... was noted on the cross-index plat and is

assigned page No. 3985 in book No.

oss Index No. L 25 T 30 N

30W

Form 125-3690

T30N R30W R29W 1/4 513 518 1/4 5/8 BT