## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T30N R30W Montana Principal Meridian G.L.O. notes book3420 page 9 has the notes for the meander corner but the copies we received were illegible. Found a BLM brass cap marked T30N R30W

S14 S13

- 1) 12" tamarack bearing S65°E 42 lks., scribe ....R30W (the rest is covered)
- 2) 18" fir bearing S312°W, 30 lks., marked T30N R30W S13 MC BT

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: May 14

No added monumentation

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See sketch on reverse side

ONTAN JOHN C. **ERICKSON** 

3979 S

SURVEYON

Surveyor's Seal

James R. Staples

certify that the information shown herein is true and correct.

James K. Staples Signature of Ground Party Chief

JOHN C. ERICKSON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this

recordation form and approve the same. Signature of Surveyor

3979 5 Registration Number

DIAGRAM OF CORNER: T30N R30W

13 14

= Corner recorded on the sheet

Office of Clerk and Recorder, County of ...

This "corner record" was filed for record on the BE day of Mar

19.57, was noted on the cross-index plat and is

assigned page No. 3985 in book No.

30W

Cross Index No. T. 30N R.

MC

