

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T30N R30W Montana Principal Meridian G.L.O. notes book 3420 page 20 has limestone 18x9x8 12" in the ground with 2 bearing trees. Found the stone and both bearing trees.

Record: 12" pine bearing S25°W, 32 lks., marked 1/4 S16 BT
Found: 12" pine dead bearing N66°W 32 lks., marked 1/4 S16 BT

Record: 12" fir bearing N31°E, 24 lks., marked 1/4 S15 BT
Found: 18" fir bearing S58 1/2°E, 24 lks., with overgrown blaze (re-scribed)

It appears that when the original bearings were recorded they were recorded 90 off.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work June '70


Replaced the original stone with Corps of Engineers brass cap. See sketch on reverse side.

1 new bearing tree - 6" fir bearing N65°W, 21 lks., marked 1/4 S16 BT

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side

Surveyor's Seal



I, James R. Staples
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, JOHN C. ERICKSON
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

3979S
Registration Number

DIAGRAM OF CORNER:
T30N R30W



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 28 day of Mar 19 89, was noted on the cross-index plat and is assigned page No. 4025, in book No. 113

County Official

N

