INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- Description of monument and accessories set to perpetuate the corner position.
 Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner N 1/16 Section 4 T. 30 N. R. 30 W., P.M.M. Lincoln County 1975 Certified Corner Recordation No. 382, by J. Ninneman, 534ES: Not set. Falls in Mt. Hwy. 37 pavement. II. No monuments found. III. At the calculated position, I set a 3/4 in. diam. x 30 ins. long aluminum rod, 30 ins. in the ground, with 3 1/4 in. diam. U.S.D.A. aluminum cap marked as shown. N 1/16 \$5 S4 7322-\$ 1989

Established two bearing trees:

- A Douglas fir, 12 ins. diam., bears N 29 W, 52.9 ft. dist., scribed N1/16 S5 BT.
- A Douglas fir, 13 ins. diam., bears S 60° E, 81.7 ft. dist., scribed N1/16 S4 BT.

Painted a red band around each bearing tree and attached Survey Monument and Bearing Tree signs. This corner falls in the highway fill between the highway and a private driveway. Did not set a guard post. Declination 19 East.

