

INSTRUCTIONS


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner of Secs. 11, 12, 13, 14 T. 30 N., R. 30 W., P.M.M., Lincoln County

- I. 1898 G.L.O. original record by Paul S.A. Bickel: Set a stone monument and mound of stone W.

1968 B.L.M. remonumentation record by Woodrow E. Damm et al: "The cor. of secs. 11, 12, 13 and 14, monumented with a limestone, 16 x 9 x 4 ins., firmly set, mkd. with 4 grooves on the S. and 1 groove on the E. faces. At the corner point, set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A boulder outcrop, 4 x 3 x 2 ft. above ground, bears N58° E, 24 lks. dist., mkd. X BO, 6 ins. below top of SW face.

Bury the original stone alongside the iron post."

- II. Found, a 2 1/2 in. diam. iron pipe, 2 ins. out of the ground with a 3 1/4 in. diam., B.L.M. brass cap marked as shown above, from which

A rock outcrop 23 x 25 x 3 ft. (recd: 4 x 3 x 2 ft.) above ground, bears N58° E, 15.2 ft. (23 lks.) dist. marked X BO. (B.L.M.)

- III. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, East, 3 ft. No bearing trees available within limits. Magnetic Declination: 20° 30' East



SKETCH OF CORNER

CERTIFICATION

I, Gary C. Crismon
certify the information shown herein is true and correct.


Gary C. Crismon
Signature Ground Party Chief

I, Alvah F. Hughes
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.).

Alvah F. Hughes
Signature of Surveyor & Seal

Date: 12/26/89 Reg. No. 7322-L9

Employer: U.S. FOREST SERVICE



Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Dec 29, 1989 was noted on the cross-index plat and is assigned page No. 4184, in book No. _____

Cross Index No. J-21 T. 30 N. R. 30 W. P.M.M.

