## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

## **CERTIFIED CORNER RECORDATION**


W 1/16 of Secs. 19/30 Lincoln Corner\_ 1981 corner recordation by Jack H. Ninneman: Set a capped 5/8" x 24" steel rod (stamped JHN 46618) from which

A 7" fir bears S5  $^{\circ}$ E 3.4 ft. scribed W 1/16 S 30 BT and posted. A 8" fir bears N80  $^{\circ}$ W 10.5 ft. scribed W 1/16 S 19 BT and posted.

II. Found a 5/8 in. diam. rebar with yellow plastic cap mkd. JHN 4661S. from which

> A douglas fir, 8 ins. diam., bears  $85^{\circ}E$ , 4.4 ft. dist., healed face. (Record 3.4 ft) A douglas fir, 9 ins. diam., bears N80  $^{\circ}$ W, 10.7 ft. dist., healed face.

III. At found JHN rebar, I set a 3/4 in. diam., 30 ins. long alum. rod, 26 ins. in the ground with alum. cap mkd. as shown:



Painted red bands around the bearing trees and attached Land Survey Mounument and Bearing Tree signs. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, West, 3 ft.

Magnetic Declination: 20 East.

