CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found a BLM brass cap marked as shown.

From which: A 6" dead douglas fir bears N10°E, 52 lks.(Sec. # BT)

A 28" ponderosa pine bears N47°W, 107 lks.(Sec 6 BT)


1964 BLM Record: Set an iron post with brass cap from remains of

original evidence.

From which: A pine 20" diam. bears N47°W, 107 lks dist.

A fir 6" diam. bears N10°E, 52 lks dist

Bury original stone alongside of the iron post.



DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 1979

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 752

Surveyor's Seal



I, Anthony J. Bachman certify that the information shown herein is true and correct.

Inthony J. Backma)
Signature of Ground Party Chief

I, Thomas C. Hill
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

Signature of Surveyor

561.2S

DIAGRAM OF CORNER:

N. T30N R30W SEC 6 SEC 5

Corner recorded on the sheet

5612S Registration Number

Office of Clerk and Recorder, County of	2)
This "corner record" was filed for record on the 311. day of	March 1980, was noted on the cross-index plat and is County Official Legity Beet,
	Cross Index No. <u>F5</u> T 30 R 30 Mer.