## CERTIFIED CORNER RECORDATION

Corner: W 1/4 Sec. 14 Twp. 30N., R.31 W., P.M.M.

**Lincoln County Montana** 

Record:

Per BLM records of 1973 Johnnie R. Mendez-Cadastral Surveyor

From the 1/4 sec. cor. of secs. 14 and 15, reestablished by J.W. Ninneman, RLS No. 534, in 1966, determined from ties as shown on plats of subdivisions, and is recorded in the Lincoln County Courthouse. This point has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 20 ins. long 21/2 ins. diam. 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 30 N., R. 31 W

1/4

S15 | S 14

1973

From Which:

A Fir, 24 ins. diam. bears S. 191/3° W., 271 1ks. dist., mkd. 1/4 S15 BT.

An X. chiseled on a concrete sidewalk, bears S. 731/2" W., 80 lks. dist.

The NE cor. of a brick church (L.D.S.)., bears S. 57 1/4" W., 348 lks. dist.

Found Evidence:

A 3 1/4 inch BLM Brass Cap marked

T 30 N., R.31W

1/4

S15 | S 14

1973

The NE cor. of a brick church (L.D.S.) bears S 87 1/2" W., 348 lks. dist.

Perpetuation:

Established the following two bearing objects: For the West 1/4 of Section 14.

From Which:

A steel fence post bears S 74° E 13.4 ft dist. for Sec. 14

A steel fence post bears N 74° W 22.9 ft dist. for Sec. 15

Attached warning and bearing tree signs to both posts.

A fire hydrant bears S 89° E 129.9 ft dist.

A fire hydrant bears S 23° E 47.4 ft dist.

A fire hydrant bears 5 25° E 47.4 ft dist.			
Declination 18 °E	1 514		OFFITIOA TION
era 1 . A **	•		CERTIFICATION
STEEL D. N. JOHN			I, \ George Clark
	5.89E	fire	certify the information shown herein is true and correct
-N	30 S 72 130 97 O	Tanhous	Thimas O I have
BLM	S74 E 129 9	nya - ozn-	Signature of Ground Party Chief
- <sup>-</sup>	1\ JCT	L Post	I, Ken Davie, RLS
1 515	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	LPOST	certification to the Control of the
	ι β.		orunder my directorisin compliance with the "Corner Recordation
W	ola,		
Νt	1 4/0		( FOLE 2-101, at see M. Can by
1/1	W P		
1	1 1	'	P. Signature of Surveyor & Seal &
1	λ ,		10 Date NOVILLE Red NOV 4975-5
	Ofire Hydrant		mployed Davis Surveying Inc.
	Hydrani		
Sketch of Corner	,		
	$\mathcal{L} + \rho$		Section
Office of Clerk and Recorder, County of finish.  This "corner record" was filed for record on 1/1/1/1/1.			
This "corner record" was filed for record on 11/16/6/			
was noted on the cross-index plat and is assigned page NoU 3 4 3			
in book No. Coral M. Cumming Ly Dis			
	County Official	7 145	
Cross Index No. Twp. 30 N., R. 3 W., P.M.M.   ● THIS CORNER			t .