

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SW - SE 1/64, Section 4, T. 30 N., R. 31 W., P.M.M., Lincoln County


1. CORNER SET BY INTERSECTION OF 1/64 LINES PER BLM MANUAL

-SET 5/8" REBAR WITH YELLOW PLASTIC CAP STAMPED J.H.N. 4661 S

-NO BT'S SET

SW 1/4, SE 1/4, Sec. 4

CS 1/16



S 1/4

E 1/16

SKETCH OF CORNER

SET 5/8" X 24" CAPPED
STEEL PIN STAMPED:
J.H.N. 4661 S



CERTIFICATION

I, David Stanley

certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Jack H. Ninneman

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Jack H. Ninneman
Signature of Surveyor & Seal

Date: 4/4/83 Reg. No. 4661 S

Employer: NINNEMAN ENGINEERING, INC.


Office of Clerk and Recorder, County of LINCOLN. This "corner record" was filed for record on the APRIL 7 day of 1983 was noted on the cross-index plat and is assigned page No. 2197, in book No. Janet BF Siegel by Betty L. Conces

County Official

deputy

Cross Index No. DE-11.12 T. 30 R. 31 P.M.M.

Sec. 4



• - corner this sheet