

1. Original and/or substitute record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner C - W - SW - SE 1/256, Sec. 4, T. 30 N., R. 31 W., P.M.M. Lincoln County


I. CORNER SET BY SINGLE PROPORTION

-SET 5/8" REBAR WITH YELLOW PLASTIC CAP STAMPED J.H.N. 4661 S

-NO BT'S SET

SW 1/4, SE 1/4, Sec. 4

CS 1/16



S 1/4

E 1/16

SET 5/8" X 24" CAPPED
STEEL PIN STAMPED:
J.H.N. 4661 S



SKETCH OF CORNER

CERTIFICATION

I, David Stanley
certify the information shown herein is true and correct.

Signature Ground Party Chief


I, Jack H. Ninneman
certify that this Corner Record correctly represents work performed
by me or under my direction in compliance with the "Corner
Recordation Act" (70-22-101, et seq., M.D.A.)

Jack H. Ninneman
Signature of Surveyor & Seal

Date: 4/4/83 Reg. No. 4661 S

Employer: NINNEMAN ENGINEERING, INC.

Office of Clerk and Recorder, County of LINCOLN. This "corner
record" was filed for record on the APRIL 7 day of 1983
was noted on the cross-index plat and is assigned page No. 2199, in
book No. _____ Janet BF Seigel by Betty L. Conces
County Official deputy



Cross Index No. D.E. 11, 12 T. 30 R. 31 P.M.M.

• - corner this sheet