
CERTIFIED CORNER RECORDATION

Corner EWW 1/256 Sec. 26&35 T. 30N R. 31W P.M., MT Lincoln County

I. 1974 B.L.M. survey by Hjellam and Pritchard: Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap.

1983 Corner Recordation filed in Lincoln County Courthouse by Melvin D. Lauteren #4232-S: Found a 2 1/2 in. diam. iron pipe, projecting 5 ins. above ground, in a collar of stone, with brass cap mkd. as shown.



from which:

A mound of stone, 2 ft. diam., East of corner.

Established two new bearing trees:

A pine, 10 ins. diam., bears S61°W, 32.4 ft. dist., mkd. "1/256 S35 BT". A pine, 8 ins. diam., bears N17°W, 7.0 ft. dist., mkd. "X BT".

Set a steel post with a "Land Survey Marker" decal, 1 ft. SW of corner.

II. Found a 2 1/2 in. diam. iron pipe, 2 ins. above ground, firmly set in a collar of stone, with a 3 1/4 in. brass cap mkd. as shown above, from which:

A pine, 10 ins. diam., bears S61°W, 32.4 ft. dist., with visible scribing.

A pine stump, 8 ins. diam., bears N17°W, 7.0 ft. dist., with "BT" visible.

A rock mound, East.


A steel guard post, with LSM and PB decals, South, 1.5 ft. distant.

III. Established one new bearing tree:

A pine, 5 ins. diam., bears \$29°W, 28.8 ft. dist., scribed "X BT".

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East



Office of Clerk and Recorder, County of ______. This "corner record" was filed for record ______ on _____ was noted on the cross-index plat and is assigned page No. 9739 in book No. ______ CORAL M CUMMINGS _____ County Official By PLB

- corner this sheet

ross Index No. V-17.75

^{7.} 30N ^{R.} 31W ^{PM}