

CERTIFIED CORNER RECORDATION

7
CORNER S1/4 S31 S6 T. 29 N., R. 33 W., P.M.M. LINCOLN COUNTY

RECORD:

Refer to attached GLO notes

FOUND EVIDENCE:

A 5/8 inch dia. rebar capped with white plastic cap

A 18 inch DBH Hemlock with overgrown scribe bears S74°E 8.8 ft. dist.

A 12.5 inch DBH Cedar scribed 1/4 S6 T30N R33 BT bears N82°W 10.4 ft. dist.


PERPETUATION:

Set a 2 1/2 inch dia. pipe 30 inches long 24 inches in the ground with a 3/4 inch Aluminum cap stamped (see diagram below)

MAGNETIC DECLINATION: 16° E

12.5" CEDAR

N 82° W
10.4'



DIAGRAM

S 74° E
8.8'
18" HEMLOCK



CERTIFICATION

I, Clerk Williams
Certify the information shown herein is true and correct
Signature of Ground Party Chief

I, [Signature]

certify that this corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-21-101 et seq., M.C.A.)


Signature of Surveyor & Seal
Date: 11/10/2009 Reg. No. 1975-3

Employer: Davis Surveying, Inc

SKETCH OF CORNER

Office of C 222801 BOOK: CCR CC&R'S PAGE: 11333 Pages: 1
This "corne STATE OF MONTANA LINCOLN COUNTY
was noted: RECORDED: 11/10/2009 3:47 KOI: CC&R'S
No. TAMMY D. LAUER CLERK AND RECORDER
In book No FEE: \$0.00 BY: [Signature]
TO: DAVIS SURVEYING, INC. P.O. BOX 896, TROY, MONTANA 59935

SECTION



THIS CORNER

Cross Index No. T. 29 & 30 N., R. 34W., P.M.M.