	CERTIFIED CORN	NER RECO	ORDATION	
Corner CS NE 1/6	4 T 30 N	N. R. 34 V	<u>V.</u> Р.М.М	<u>Lincoln</u> County
I. Record: None				
II. <u>Found:</u> No reco	rd monuments found.			
III. Damahantiana	 	made and buy a		O in a diam
steel	At the corner point, dete rebar 24 ins. long, 23 in Inum cap marked as sho	ns. in the gr	ound, with a 3	
A cedar, 2	4 ins. diam., bears N51°E	., 16.30 ft. c	list., scribed X	вт.
A Hemlock	fir, 18 ins. diam., bears	N8'W, 17.00	ft. dist., scribe	d X BT.
		ands to all b	earing trees an	d attached
		set monum	ent with attach	ed
Magnetic de	eclination: 18° East			
Equipment	used: Hand compass and	i loggers tap	e	
			/ T30N R	34W \
	ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces to bears 2.70 ft. East of set monument with attached nument decal. ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees and attached ee signs. ** Ces and 6 in. wide red bands to all bearing trees			
			7322	LS
			201	
	nty Records for additiona			
Kootenai Surveyors	Inc., 314 California Av.,	Libby, MT. 5	9923 (406) 293	3-4354 NOT
Sales 2011 7" H	Hemlock Fir			**************************************
	A	1		
7.00	22" Ced	ar 🏌	-	
7.7	16.30 ft.	5	certify that this Corner performed by me or un	JONES Record correctly represents work nder my direction in compliance with
•			/DI. ~	2 1/2 200
		7	Signature of Date: 11/11/2011	Surveyor & Seal
SK	ETCH OF CORNER			i Surveyors Inc.
Office of Clerk and Records	l in colm	This "co	rner	
record" was filed for record	•			Sec. 2
235959 BOOK: CCR CCGR'S PAGE: 11923 Pages: 1 was noted on the cross—it STATE OF MONTANA LINCOLN COUNTY				
book No.	RECORDED: 11/16/2011 9:0 TAMMY D. LAUER CLERK AND		۔ ۔ ت رہ	
	FEE: \$0.00 BY:	Eannix	BY, MT 59923	
Cros	ss Index No.	т. <u>30N r. 3</u>		
	, Montana Board of Profession	al Engineers &		 corner this sheet
				• corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors