

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Section Corner Common to Sec. 5, Sec. 6, Sec. 7 & Sec. 8 of Twp. 30 N.,
R. 33 W., M.P.M.
Point for Corner fell in long established road.
All evidence destroyed

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Completed
Date of work: Dec. 1969
Cor. # 1 Sec. Corner Common to Sec. 5, Sec. 6, Sec. 7 & Sec. 8 of Twp. 30 N., R. 33 W., M.P.M.
Set by double proportionate distances a 2" Pipe 30" long with orange plastic plug in the
ground from which a 10" Cottonwood Bears N 69° E 80 Ft. Marked S 5 BT a 12" Cottonwood
Bears S 58° W 58.4 Marked S 7 Bt.
Cor. # 2 Set Steel Pin
Cor. # 3 Set a steel pin from which a 10" Pine Bears S 41° E 17.2 Ft. Marked 1/16 E
8" Pine Bears S 48° W 18.2 Ft. Marked 1/16 E
Cor. # 4 Set a steel pin from which a 10" Pine Bears S 87° 40' E 17.8 Ft. Scried 1/4
A 12" Pine Bears N 57° 30' E 16 Ft. Scried 1/4 S 6 Bt
Cor. # 5 Set a steel pin
Cor. # 6 Set a steel pin
Cor. # 7 Set steel rod in oil pavement from which a 12" Cottonwood Bears S 71° E 66 Ft.

SEE BACK OF SHEET
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

DIAGRAM OF CORNER:

Surveyor's Seal

I, Jack H. Ninneman
certify that the information shown herein is true and
correct.

N.

Jack H. Ninneman
Signature of Ground Party Chief

I, Jack W. Ninneman
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Jack W. Ninneman
Signature of Surveyor

= Corner recorded on the sheet

Montana 534 ES
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 24th. day of February 19 70, was noted on the cross-index plat and is
assigned page No. 171, in book No. 1
ELEANOR L. VAUGHN, By: *Mac Watson*
County Official Deputy.

Marked N 1/16

Cor. # 8 Set a steel pin

Cor. #9 Set a steel pin from which a 6" Pine Bears S 43° W 12.9 Ft.

Scribed NE 1/16 An 8" Larch Bears N 28° W 8.7 Ft. Scribed NE 1/16

Cor. # 10 Standard Brass Cap by BLM

Cor. #11 Set a "Lifetime" Plastic Marker from which a 12" Fir Bears N $8^{\circ}21'$ W
21.6 Ft. Scribed 1/16 S

Cor. #12 Set a "Lifetime plastic marker from which a 10" Pine Bears N $82^{\circ}30'$ E 11.2 Ft.
Scribed C 1/16 S A 8" Pine Bears S $58^{\circ}19'$ W 6.7 Ft. Scribed 1/16

Cor. #13 Set "Lifetime" plastic marker

Cor. #14 Set "Lifetime" plastic marker

