

**INSTRUCTIONS**

1. Original and subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION**

Corner CW 1/16 th. Sec. 19 T. 30N. R. 33W. P.M.M. Lincoln County

Set 5/8" x 18" steel rebar with yellow P.V.C. cap stamped: KED 4975 S for CW 1/16th corner. From which I scribed and marked two new bearing trees.

- 1) Douglas fir 8 inches in dia. bears S 21° W, 22.4 feet in distance, scribed CW, 1/16, S 19 Bt.
- 2) Douglas fir 8 inches in Diam. bears N 83° 45' W, 18.5 feet in distance, scribed CW, 1/16, S 19 BT.

Painted the face scribe and red bands around each bearing tree and attached a bearing tree sign on each.

<p align="center"><b>SKETCH OF CORNER</b></p>	<p align="center"><b>CERTIFICATION</b></p> <p>1. <u>Kenneth E Davis</u> certify the information shown herein is true and correct.</p> <hr/> <p align="center">Signature of Party Chief</p> <p>1. <u>Kenneth E Davis</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)</p> <hr/> <p align="center">Signature of Surveyor &amp; Seal</p> <p>Date: <u>2/23</u> RD Reg. No. <u>4975 S</u> Employer: <u>Davis Surveying Inc</u></p>
---	---

Office of Clerk and Recorder, County of Lincoln This "corner record" was filed for record on the Feb. 24 day of 1989 was noted on the cross-index plat and is assigned page No. 3980, in book No. \_\_\_\_\_

Grant B. Segelby  
County Official

