Original are subsequent record used to evaluate the corner position.
Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

3. Description of monument and accessories set to perpetuate the corner position

Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

C 1/4 Section 20 T. 30 N. R. 33 W P.M.M. Lincoln _County

I. Davis Surveying, Inc. 1992 (June)

I set a 5/8 inch dia. x 24 inch long rebar with a $1\frac{1}{4}$ inch dia. plastic cap stamped: KED 4975 S

FROM WHICH:

A 5 inch DBH Cedar bears N $30\,^{\circ}\text{E}$ 5.21 feet from the center of the tree, scribed: $C_{\frac{1}{4}}$ S 20 BT (Notch at Root Crown)

A 6 inch DBH Cedar bears S 36°W 35.33 feet from the center of the tree, Secribed: C^{1}_{4} S 20 BT (Notch at Root Crown)

MAINTENANCE:

Painted BT and Land Survey Monument signs.

Painted blazes red.

Painted a red band around the tree above the BT sign.

Set a steel post with Land Survey Marker Sticker 1 foot North of the corner.

Declination = 20° E CERTIFICATION <u>Kent Davis</u> 50BH ation shown herein is true and correct. CEDAR N30°E nature Ground Party Chief 5.2 6"DBH certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-10) To seq., M.C.A.) CEDAR 536W 35.55 Signature of Surveyor & Seal Reg. No. 4975 S Employer: Davis Surveying, Inc. SKETCH OF CORNER Office of Clerk and Recorder, County of Lencola record" was filed for record on Oct 14, 1992 was noted on the cross-index plat and is assigned page No. _ CorolM Cummings by book No. _ County Official

· corner this sheet

Cross Index No. .