CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 10/5/80

Set standard aluminum post & cap 24ⁿ in the ground Bearing trees;

18" Larch N. 9° W. 18.7 feet

Mkd. N 1/16 S 25 BT

16" Doug. Fir S. 80° W. 28.0 feet

Mkd. N 1/16 S 25 BT

Bearing tree tags affixed & location poster
Brass tags # 2968 S set at base of BTs at root crown distance from corner

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Survey Plat, South Fork Keeler, T. 30 N., R. 34 W., P.M.

I, Milton I. Booth

certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Milton I. Booth

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Mullin Booth
Signature of Surveyor

2968 S Registration Number DIAGRAM OF CORNER:

N 16 | 5 25 | 980 = Corner recorded on the skeet

Office of Clerk and Recorder, County of Line Late day of Leptanhau 1981, was noted on the cross-index plat and is assigned page No. 1185, in book No.

Cross Index No. 5-23 T. 30N R. 34W F. Mer.