CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

N. 10° E. 64 Pine 9 Lks. (Found) S. 46° E. 64 Lks. Pine (Found)

s. 72° W. Pine 44 Lks. Found)

N. 11° W. 9 Lks. (Found)

Granite Stone 1 Notch on E, 5 Notches on W. (Found)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 8/4/80

Set standard aluminum post & cap, buried rock alongside.

New Bearing trees;

14 Larch N. 42 W., 23.8 feet Mkd. T30N R34W S35BT 14" Doug. Fir N. 53° E. 13.2 feet
12" Doug. Fir S. 53° W. 8.0 feet
8" Doug. Fir S. 50° E. 22.2 feet Mkd. T30N R34W S36BT Mkd. T29N R34W S 2BT Mkd. T29N R34W S 1BT

Bearing tree tags affixed & Location poster Brass tags #2968 S set at base of BTs at root crown distance from corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Survey Plat, South Fork Keeler, T. 30 N., R. 34 W., P.M.



certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Milton I. Booth

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2969 S Registration Number

DIAGRAM OF CORNER: 36 29685 1980 = Corner recorded on the sheet

Office of Clerk and Recorder, County of This "corner record" was filed for record on the . . day of elemen) was noted on the cross-index plat and is assigned page No......, in book No...... County Official

Cross Index No. Z · 2/ T JON R R34W Mer.