1. Original and/or subsequent record used to evaluate the corner p 2. Descriptive of evidence found, note discrepancies in the record, state method of columbiating tool or obliterated unest and accessories set to perpetuate the corner posit 3. Description of Sketch or curner, show all pertinent data which can best be shown in a stoich example, curner marking lopography lies, position of seen meries, pic. Certification must be algord and sealed by Registered Land be
Fill in Cross index & Section Diagram at bottom of about. **CERTIFIED CORNER RECORDATION** Corner <u>N-N-S 1/256</u> Sec. 24 T. 30N R. 34W P.M.M. .County No record or evidence of corner being previously set. I position corner from found section and quarter corners and as shown on the Certificate of Survey as filed and af record in the Lincoln Co. Courthouse. I set a 3" alum. cap for corner position, from which: A 12" tamarack bears N48°E, 21.7', scribed N-N-S 1/256 S24 BT A 9" tamarack bears N25°W, 28.4', scribed N-N-S 1/256 S23 BT Painted bands around BT's and painted the blazes red. Posted BT, Attention, and Locations signs. CERTIFICATION GENE certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner" No. 27346 MOUNTAIN SURVEYORS SKETCH OF CORNER Office of Clerk and Recorder, County of LINCOLN - . This "corner record" was filed for record on the Nov 30 was noted on the cross-index plat and is assigned page No. 2786

- 30N - 34W

book No. _