## INSTRUCTIONS

 Original and/or a quent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of corners.

3. Description of monument and accessories set to perpetuate the corner position.

4. Sketch of corner, show all perfinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

topography in the position of accessors (e.g., form).

5. Certification must be signed and scaled by Land Surveyor registered in the State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner NW Cor. Sec. 3 County T. 30 N R. 34 W P.M.M. <u>lincoln</u>

I. 1903 GLO record: Set a quartz stone, 16x10x6 ins., 11 ins. in the ground for closing cor. of secs. 3 and 4, marked C C on S face, with 3 grooves on E and W faces; from which

> A hemlock, 16 ins. diam., bears S48½°E, 55 lks. dist., marked T30N R34W S3 BT

> A hemlock, 14 ins. diam., bears S20½°W, 71 lks. dist., marked T30N R34W S4 BT

II. Found: A set stone - CC on S., 3 grooves E. and 3 grooves W. sides are visible; from which

A stump, bears S48°E, 55 lks. dist., scribe visible. A 50 Ft. high snag; bears S20½°W, 71 lks., all scribe visible.

III. Perpetuation: Set a 6 Ft. galvanized steel post with "Survey Marker" decal attached, bears West, 2 lks. dist.

> Painted red: 6 in. bands and scribe blazes, and posted "Bearing Tree" and "Survey Monument" signs on bearing trees.

	<u> </u>
·	CERTIFICATION
	1. Gary C. Crismon
•	certify the information shown herein is true and correct,
	Say C. Cismon ON April.
	Signature Ground Party Chief
$\circ$	1. HUAH F. Hugies
	by me or under my direction in company to the popular of the company of the compa
Chr.	Recordation Act 700-22-101, et segs 45 1977 3 2 121
20 143. 3 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	along to become
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Signature of Surveyor A Stell
SNAG OF	Date: 3/8/89 Reg. No. 7322-40 [AKO]
SKETCH OF CORNER O STUMP	Employer: U.S.F.S.
Office of Clerk and Recorder County of Lincoln	Sec. 3
Office of Clerk and Recorder, County of	This "corner
record" was filed for record on	
	3980 in
	, In - / -   -   -   -   -   -   -   -   -
book No first BF Sugal	by Dul Dischiff
County Off	icial Day
1.3	
Cross Index No. H-/3	T 30N R 34W PMM • corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors