INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- Description of monument and accessories set to perpetuate the corner position.
- Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 Certification must be signed and scaled by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED	CORNER	RECOR	DATION
OFILITIES.	COMITEIN	IVECOI	DAIIDI3

C 1/4 of Sec. 2 30 N., 34 W., Corner _ P.M.M. County

- No records found at Lincoln County Courthouse.
- II. No evidence on the ground.
- III. At the determined corner position by survey, set a 3/4 ins. dia. aluminum rod, 30 ins. long, 26 ins. in the ground with attached 3 1/4 ins. dia. U.S.D.A. Forest Service aluminum cap, marked as shown:

TRON RRAW c 1/4 s2 7322LS 1991

from which

A cedar, 6 ins. dia., bears $S28^{\circ}$ W, 19.9 ft. dist., mkd. C 1/4 S2 BT. A grand fir, 7 ins. dia., bears West, 9.7 ft. dist., mkd. C 1/4 S2 BT.

Set a 6 ft. galvanized steel guard post with "Survey Marker" and "Property Boundary" decals attached. 3 ft., North.

Painted a red band around each bearing tree and attached "Land Survey Monument" & "Bearing Tree" signs.

Magnetic Declination: East. 20

CERTIFICATION certify the information shown herein is true and correct. enneth Alvah F. Hughes certify that this Corner Record correctly represents work perfo Ν 11/13/91 U.S. FOREST SERVÍCE

SKETCH/OF CORNER				. 0.
Office of Clerk and Recorder, County	of Lincoln		Sec. 2	ا م
ecord" was filed for record on	4-22-92			
vas noted on the cross-index plat and	is assigned page No.	957, in	├ ─┼─ ┿ ─┼	
oook No.	County Off	-	 	
	C19 Cross Index No.	30 N 34 W T R PMN	• - corner this s	 heet

· corner this sheet ____ T, _____ PMM