
INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- corners.
 3. Description of monument and accessories set to perpetuate the corner position.
 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 6. Fill in Cross Index & Section Diagram at bottom of sheet.

C	EI	R	T	Ш	FI	E	D	C	0	R	N	EF	₹	₹I	E($\mathbb{C}($	D	R	D	Α	T	1	D	N	l
---	----	---	---	---	----	---	---	---	---	---	---	----	---	----	----	---------------	---	---	---	---	---	---	---	---	---

30 N., C E 1/16 Sec. 2 34 W., P.M.M. Corner _ County

- No record found at Lincoln County Courthouse
- II. No evidence on the ground
- III. At the determined corner position by survey, set a 3/4 ins. dia. aluminum rod, 30 ins. long, 26 ins. in the ground with attached 3 1/4 ins. dia. U.S.D.A. Forest Service aluminum cap, marked as shown:



A grand fir, 14 ins. dia., bears $832^{\circ}W$, 48.8 ft. dist., mkd. CE 1/16 S2 BT. A birch, 7 ins. dia., bears $832^{\circ}W$, 45.0 ft. dist., mkd. CE 1/16 S2 BT.

Raise collar of stone around monument.

Set a 6 ft. galvanized steel guard post with "Survey Marker" and "Property Boundary" decals attached, 4 ft. South.

Painted a red band around each bearing tree and attached "Land Survey Monument" & "Bearing Tree" signs.

Magnetic Declination: East, 20

7" BIRCH \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	CERTIFICATION Kenneth Kern certify the information shown herein is true and correct. Kenneth Kern Signature Ground Party Chief
2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Alvah F. Hughes certify that this Corner Record correctly represents work performed by me or under my direction in compliance with, the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) Signature of Surveyer & Scaly Date: 11/13/91 Reg. No. 7322 L\$
14" FIR TSKETCH OF CORNER	Employer: U.S. FOREST SERVICE STER

SKETCH OF CORM	NER	Employer: U.S. FO	REST SERVICE SIENT
Office of Clerk and Recorder, County of	Lincole	. This "corner	Sec. 2
record'' was filed for record on			
was noted on the cross-index plat and is	assigned page No		
oook No	County	Official	
	C20	30 n 34 w	
•	Cross Index No.	T PMM	corner this sheet