- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking. 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

1 of MS 7655 T. ______R. ____P.M.M. Lincoln Corner. _County


1905 MS original record by E.P. Harrison: "A post, 5x5 ins. , 5 ft. long, 2 ft. deep. scribed 1-7655. Raised a mound of stone around post.

A blazed tamarack tree, 12 ins. in diam., scribed BT 1-7655. bears N15 $^{\circ}$ E, 9.4 ft. A blazed tamarack tree, 14 ins. in diam., scribed BT 1-7655, bears N50°w, 7.4 ft."

II. A mound of stone, 2 ft. base, 1 ft. high, with rotten remains of post. From which:

A dead larch, 14 ins. diam., bears N55 W, 7.1 ft. dist., mkd. BT 1 7655.

III. Set a 3/4 in. diam., 30 ins. long, alum. rod 26 ins. in the ground with alum. cap mkd. as shown.



From which:

A fir, 6 ins. diam., bears N28 E, 14.6 ft. dist., mkd. 1 7655 BT. A fir, 5 ins. diam., bears S25 E, 3.5 ft. dist., mkd. 1 7655 BT.

Painted red bands around the bearing trees and attached "Land Survey Monument" and "Bearing Tree" signs.

Set a galvanized steel guard post with "Land Survey Marker" and "Property Boundary" decals, $N44^{\circ}W$, 3 ft. Magnetic declination: 20° East



CERTIFICATION

Todd Kevin A.

Pearson Ronald A.

certify that this Corner Record correctly represents work performed by me or under my direction in compilance with the "Corner

Signature of Surveyor & Seal

Date: 11/23/92 Reg. No. 9008 LS

U.S. FOREST SERVICE

SKETCH OF CORNER

Office of Clerk and Recorder, County of . . This "corner 12-15-92 record" was filed for record on ___ was noted on the cross-index plat and is assigned page No. _ book No. _ County Offici

Cross Index No. -

1 MS 7655

Sec

corner this sheet