## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

  5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

3 of MS 7655 P.M.M. \_County Corner\_

1905 MS original record by E.P. Harrison: I. Raised a mound of earth around post.


A blazed tamarack tree, 24 ins. in diam., scribed BT 3-7655, bears N45 $^{\circ}$ E. 3 ft. A blazed fir tree, 16 ins. in diam., scribed BT 3-7655, bears \$10°E, 11 ft."

II. Found a post hole with rotten remains.

From which:

A larch, 29 ins. diam., bears N45 E, 3.0 ft. dist., visible scribing. (Original BT) A dead fir, 26 ins. diam., bears S10 E. 11.0 ft. dist., healed face. (Original BT)

III. Set a 3/4 in. diam., 30 ins. long. alum. rod 24 ins. in the ground with alum. cap mkd. as shown.



From which:

book No. -

A fir, 7 ins. diam., bears  $N84^{\circ}W$ , 17.7 ft. dist., mkd. 3 7655 BT.

Painted red bands around the bearing trees and attached "Land Survey Monument" and "Bearing Tree" signs.

Set a galvanized steel guard post with "Land Survey Marker" and "Property Boundary" decals. S15 W, 3 ft. Magnetic declination: 20 East



· - corner this sheet

CERTIFICATION Kevin A. Todd Ronald A. Pearson certify that this Corner Record correctly represents work performed by me of under my direction in compliance with the "Corner in compliance et seq., M.C.A.) 11/23/92 9008 Ls \_\_\_Reg. No. \_ 16" DEAD FIR U.S. FOREST SERVICE SKETCH OF CORNER Sec. Office of Clerk and Recorder, County of . This "corner 12-15-92 record" was filed for record on \_\_\_\_ was noted on the cross-index plat and is assigned page No.

3 MS 7655

Cross Index No.

County Off