

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 S23 | S24 T. 31 N. R. 26 W. P.M.M. Lincoln County

RECORD 1 GLO survey by Abram L. Jaqueth, July., 1893.

"Set a limestone 20 x 12 x 6 ins. 15 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, from which

- A pine tree 7 ins. diam. bears S 8° E. 11 lks. distant marked 1-4 S.B.T.
- A pine tree 8 ins. diam. bears S 57° W. 16 lks. distant marked 1-4 S.B.T."

RECORD 2 Corner Record (Search) card by Daniel C. Smiley filed in the Cadastral Dept. at the Flathead Nat. Forest Supervisors Office, Kalispell, MT., 1974.

"Found original stone scribed 1/4 on W. face.
No evidence of original bearing trees.

Set Location Posters:
#1: 15" Doug fir, S35° E, 11 ft. to corner.
#2: 12" Doug fir, S47° W, 12 ft. to corner.
Date 7/10/74."

FOUND A firm set limestone, 20 x 13 x 7 ins. showing 8 ins. above the ground with chiseled "1/4" visible on West face.

Root crowns only, remain of G.L.O. bearing trees at record bearing and distances.

Both trees as described in Smiley corner card. We now blaze and scribe them as bearing trees as follows.

SET In place of G.L.O. stone, an aluminum pipe, 2 1/2 inches in diameter, 30 inches long, 24 inches in the ground, with a 3 1/4 in. diameter aluminum cap marked as shown. We bury the G.L.O. monument with marks down alongside the East edge of pipe and establish the following BT's.

- A Douglas fir, 15 inches dbh, bears N.37° W., 11.8 feet distant, blazed and scribed "1/4 S23 BT."
- A Douglas fir, 14 inches dbh, bears N.49° E., 14.0 feet distant, blazed and scribed "1/4 S24 BT."

Measurements were made with a Silva Ranger hand compass (declination 17° E.) and a steel tape to the center of the root crowns of all trees. Distances are horizontal.

We attached "BT" and "LAND SURVEY MONUMENT" signs to the BT's.

<p align="center">SKETCH OF CORNER</p>	<p align="center">CERTIFICATION</p> <p>I, <u>Ron Krueger</u> certify the information shown herein is true and correct. <u>Ron Krueger</u> Signature Ground Party Chief</p> <p>I, <u>Daniel C. Smiley</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) <u>Daniel C. Smiley</u> Signature of Surveyor & Seal</p> <p>Date: <u>3/2/91</u> Reg. No. <u>3526ES</u> Employer: <u>U. S. FOREST SERVICE</u></p>
---	---

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Mar 11, 1991 was noted on the cross-index plat and is assigned page No. 4527, in book No. _____, in Coral McCummings by Eric Beckhoff County Official

Sec. 24	

Cross Index No. P-21 T. 31 N R. 26 W P.M.M.

• - corner this sheet

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 S24 S25 T. 31 N. R. 26 W. P.M.M. Lincoln County

RECORD GLO survey by Abram L. Jaqueth, July., 1893.

"Set a slatestone, 22 x 12 x 5 ins 17 ins., in the ground, for 1/4 Sec. Cor. marked 1/4 on N. face, and raised a mound of stone 1 1/2 ft. high 2 ft. base alongside
Pits impracticable"

FOUND A leaning slatestone, 22 x 12 x 5 ins. showing 9 ins. above the ground with chiseled "1/4" visible on North face.

A mound of stone, 3 ft. base x 1 ft. high North of slatestone.

SET In place of G.L.O. stone, an aluminum pipe, 2 1/2 inches in diameter, 30 inches long, 10 inches in the ground, with a 3 1/4 in. diameter aluminum cap marked as shown. We raise a 2 1/2 ft. diam. x 1 ft. high supporting stone collar around the alum. pipe and bury the G.L.O. monument with marks down, in base of collar and Northeast of pipe. We establish the following BT's.

A Douglas fir, 10 inches dbh, bears N.16°W., 56.6 feet distant, blazed and scribed "1/4 S24 BT."

An alpine fir, 7 inches dbh, bears S.76°W., 37.2 feet distant, blazed and scribed "1/4 S25 BT."

An alpine fir, 3 inches dbh, with a location poster attached, bears N.25°W., a distance of 28 links.

Measurements were made with a Silva Ranger hand compass (declination 17°E.) and a steel tape to the center of the root crowns of all trees. Distances are horizontal.

We attached "BT" and "LAND SURVEY MONUMENT" signs to the BT's.

10" Doug fir
N16°W
56.6 ft.
7" alpine fir
S76°W
37.2 ft.

U.S. DEPT. OF AGRICULTURE
UNLAWFUL TO DISTURB
T31N R26W
1/4 S24 S25
SMILEY 3526ES
1990
CADASTRAL SURVEY
FOREST SERVICE

CERTIFICATION

I, Ron Krueger
certify the information shown herein is true and correct.

Ron Krueger
Signature Ground Party Chief

I, Daniel C. Smiley
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Daniel C. Smiley
Signature of Surveyor & Seal

Date: 3/2/91 Reg. No. 3526ES
Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Mar 11, 1991 was noted on the cross-index plat and is assigned page No. 4528, in book No. _____ Coral M. Cummings by Bill Buckley County Official

Sec. 24

• - corner this sheet

Cross Index No. R-23 T. 31 N R. 26 W P.M.M.