

CERTIFIED LAND CORNER RECORDATION  
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 7 and 18, T31N, R28W, MPM, found original brass cap firmly set and marked (record - set A 2" iron pipe, 28" in ground with brass cap marked) from which:

A pine, 11 ins. diam, bears N 21 3/4° E - 27 Lks. Dist. alive and marked T31N, R28W, S 7 CC BT. (record - A pine, 8 ins. diam, bears N 7 1/2° E, 30 Lks. Dist, marked T31N, R28W, S 7 CC BT.)

-DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Sept. 1972

New RM

A 11 in. Larch bears S 33° E - 91 Lks. Dist.  
Marked RM

I placed signs and paint on RM and at corner

T 31 N  
R 28 W | R 28 W  
S 13 | S 7 CC  
          S 18  
1929  
(BRASS CAP)

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A.R. Trankle and Joe French  
certify that the information shown herein is true and correct.

A.R. Trankle  
Signature of Ground Party Chief

I, Stanley J. Skousen  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen  
Signature of Surveyor

DIAGRAM OF CORNER:

N. T 31 N T 31 N  
R 28 W R 28 W  
S 13 | S 7 CC  
          S 18

= Corner recorded on the sheet

2532-S  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th day of February 1973, was noted on the cross-index plat and is

assigned page No. 289, in book No. 1

Eleanor L. Vaughan, Mae Watson, Deputy  
County Official

Cross Index No. T-1 T 31 R 28 Mer.