

# CERTIFIED CORNER RECORDATION

CORNER C-W-E 1/64 S 14 T. 31 N., R. 29 W., P.M.M. LINCOLN COUNTY

RECORD:  
NONE

FOUND EVIDENCE:  
NONE

## PERPETUATION:

Set a 3 1/4 inch aluminum cap stamped (see diagram below) on a 5/8 inch dia. rebar 20 inches long.  
From which

A 6 foot steel fence post in S 14 bears N 30° W 6.8 feet.


A 6 foot steel fence post in S 14 bears S 32° E 10.0 feet.

Attached bearing tree signs to all posts.

MAGNETIC DECLINATION: 18° E

6' Steel Post

N 30° W  
6.8'



6' Steel Post

## CERTIFICATION

I, GEORGE CLARK

Certify the information shown herein is true and correct

Signature of Ground Party Chief

I, KENNETH E. DAVIS

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the

"Corner Record Act"

(Montana Code Annotated, § 2-2-101, et seq.)

Signature of Surveyor & Seal

Date 7/13/2005 Reg. No. 4975-S

By Kenneth E. Davis

## SKETCH OF CORNER

Office of Clerk and Recorder, County of \_\_\_\_\_

This "corner record" was filed for record on \_\_\_\_\_

was noted 185933 BOOK: CCR CC&R'S PAGE: 10803 Pages: 1

No. \_\_\_\_\_ STATE OF MONTANA LINCOLN COUNTY

In book N RECORDED: 07/13/2005 9:03 KOI: CC&R'S

CORAL M. CUMMINGS CLERK AND RECORDER


FEE: \$0.00

BY: Jeannie Lunn

TO: FILED

Cross Index No. C-W-E 1/64 S 14 T. 31 N., R. 29 W., P.M.M.

## SECTION



THIS CORNER