

CERTIFIED CORNER RECORDATION

CORNER C-W-E 1/64 S14 T. 31 N., R. 29 W., P.M.M. LINCOLN COUNTY

RECORD:
NONE

FOUND EVIDENCE:
NONE

PERPETUATION:

Set a 3 1/4 inch aluminum cap stamped (see diagram below) on a 5/8 inch dia. rebar 30 inches long.
From which

A 6 foot steel fence post in S 14 bears N 30° W 6.8 feet.


A 6 foot steel fence post in S 14 bears S 32° E 10.0 feet.

Attached bearing tree signs to all posts.

MAGNETIC DECLINATION: 18° E

6' Steel Post

N 30° W
6.8'



6' Steel Post

CERTIFICATION

I, GEORGE CLARK

Certify the information shown herein is true and correct

Signature of Ground Party Chief

I, KENNETH E. DAVIS

I certify that this Corner Record correctly represents work
performed by me or under my direction in compliance with the

Corner Recordation Act

70-2-201, M.C.A.

KENNETH E. DAVIS

Signature of Surveyor & Seal

D. 4975-S

Employer Is Surveyor Inc

SKETCH OF CORNER

Office of Clerk and Recorder, County of _____

This "corner record" was filed for record on

was noted on 185941 BOOK: CCR CC&R'S PAGE: 10811 Pages: 1

No. _____ STATE OF MONTANA LINCOLN COUNTY

In book No. _____ RECORDED: 07/13/2005 9:11 KOI: CC&R'S

CORAL M. CUMMINGS CLERK AND RECORDER


FEE: \$0.00

BY: Geannie Lennie

TO: FILED

Cross Index No. C-W-E 1/64 S 14 T. 31 N., R. 29 W., P.M.M.

SECTION



THIS CORNER