

CERTIFIED CORNER RECORDATION

CORNER W 1/4 S 14 T. 31 N., R. 29 W., P.M.M. LINCOLN COUNTY

RECORD:

Per GLO Paul S. A. Rickel Contract No. 329 April 8, 1898

Set a Granite Stone 18"x 10"x 10" ins. in the ground for 1-4 Sec. Cor. marked 1-4 on W face from which:

A Tamarack 18 ins. diam. bears N 86°30" E 13 lks. dist. marked 1-4 S 14 BT.

A Tamarack 18 ins. diam. bears N 16° W 36 lks. dist. marked 1-4 S 15 BT.

FOUND EVIDENCE:

NONE

PERPETUATION:

Set a 3 1/4 inch aluminum cap stamped (see diagram below) on a 5/8 inch dia. rebar 30 inches long. From which

A 10 inch DBH Douglas Fir scribed 1/4 S 15 BT. bears N 79° W 13.9 feet.


A 14 inch DBH Douglas Fir scribed T 31 N R 29 W 1/4 S 14 BT. bears S 33° E 11.2 feet.

Painted 6 inch wide bands and attached bearing tree signs to trees.

MAGNETIC DECLINATION: 18° E

10" Douglas Fir

N 79° W
13.9'



6" Douglas Fir

CERTIFICATION

I, GEORGE CLARK

Certify the information shown herein is true and correct

Signature of Ground Party Chief

I, KENNETH E. DAVIS

certify that this Corner Record correctly represents work performed by me, under my direction in compliance with the

Corner Recordation Act

2-101, Criseq., M.C.A.

KENNETH E. DAVIS

Signature of Surveyor & Seal

Date of Survey 07/13/2005 4975-S

Employer George Clark Inc

SKETCH OF CORNER

Office of Clerk and Recorder, County of _____

This "corner record" was filed for record on _____

was noted on 185943 BOOK: CCR CC&R'S PAGE: 10813 Pages: 1

No. _____ STATE OF MONTANA LINCOLN COUNTY

In book No. _____ RECORDED: 07/13/2005 9:13 KOI: CC&R'S

CORAL M. CUMMINGS CLERK AND RECORDER


FEE: \$0.00

BY: Jeanie Dennis

TO: FILED

Cross Index No. W 1/4 S 14 T. 31 N., R. 29 W., P.M.M.

SECTION



THIS CORNER