

CERTIFIED LAND CORNER RECORDATION

W 1/4 Corner for Sec. 16 Twp. 31 N., R. 29 W., M. P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

G.L.O. reports for SW Cor. Sec. 16: A slate stone 20X8X4 ins. 15 ins. in ground marked with 3 notches on south, 4 notches on east edge from which 14" larch N 56° E 45 lks. marked std. 15" larch S 41 1/2° E 56 lks. marked std. 4" Pine S 74° W 12 lks. marked std. 18" larch N 36° 45' W 46 lks. marked std.

USED STONE REPORTED.

For NW Cor. Sec. 16 A slate stone 12X10X8 ins. 8 in. in ground marked with 4 notches on S. and E. edges from which A 10" Pine bears N 54 1/2° E 29 lks. marked std. A 12" larch bears S 52° 45' E 35 lks. marked std. An 8" Pine bears S 40° W 48 lks. marked std. A 10" Pine bears N 32 1/2° W 24 lks. marked std.

USED HUB REPORTED BY C. OF E.

For W 1/4 Cor. A slate stone with two witness trees-falls in new road construction-All evidence destroyed.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Date of work: 6/12/'72

For 1/4 Cor. between Secs. 16 and 17 Twp. 31 N., R. 29 W., M.P.M.  
Set a standard brass cap monument, in concrete on north cut slope of Forest Development Road about 350 feet north of Little Jackson Creek at about Hwy. Sta. 438+60 From which  
A 12" larch bears S 27° E 94.3 feet  
Scribed 1/4 S 16 BT  
A 12" larch bears N 1° E 63.5 feet  
Scribed 1/4 S 17 BT.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE SIDE

Surveyor's Seal



I, Jack H. Ninneman  
certify that the information shown herein is true and correct.

*Jack H. Ninneman*  
Signature of Ground Party Chief

I, Jack W. Ninneman  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*Jack W. Ninneman*  
Signature of Surveyor

DIAGRAM OF CORNER:

N.  
See reverse side.

= Corner recorded on the sheet

Mont. 534 E.S.  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 25th day of July 1972, was noted on the cross-index plat and is assigned page No. 1, in book No. 275  
Eleanor L. Vaughn  
County Official

Twp. 31N., R.29W.  
M.P.M.

Coordinates and bearings  
on Montana Lambert Grid  
North Zone

Sec. Cor.  
Y585165.01  
X588462.65

REPORTED BY OTHERS  
N 70° 59' 15" E

12" LARCH

ROAD

440

G.L.O. N 0° 04' W 40 CH.  
N 4° 03' 34" E 2646.46'

N 1° E  
63.5'

7

6

Y 582 525.18  
X 588 275.30

12" LARCH

S 27° E  
94.3'

On north cut slope of  
Highway set a standard  
brass cap monument for  
¼ Corner from which a  
12" larch bears N 1° E  
63.5 feet marked ¼ S 17 BT.

A 12" larch bears S 27° E  
94.3 feet marked ¼ S 16 BT.  
Both posted.

EQUATION BK.  
PT. 436 + 94.18 AHD.  
PT. 436 + 98.42 AHD.

G.L.O. N 0° 04' W 40 CH.  
N 4° 03' 34" E 2646.46'


P.C. 428 + 84.85

100'

DEVELOPMENT

FOREST

Little Jackson Cr.



Sec. Cor.  
Y 579 885.36  
X 588 087.96