CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681,65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the % corner common to Sections 1 & 2, T31N, R29W, P.M.M. Lincoln County, Montana, we find: A cock 16" x 14" x 7" set in other rocks with one face showing, upon which is carved %; this rock is upon the edge of steep side slope over a wide gulch through which runs the Cripple Horse Creek Road; (Record: "On edge of a gulch 3 chains wide and 20' deep, set a slate stone 16 x 14 x 6 ins. 11" in the ground, for % corner marked %") from which we find, an 8" dead tamarack snag (with plain scribing facing the corner) bearing N82°E 42 links; (Record: "From which a tamarack 7" in diameter bears N82° 40°E 42 links marks 14 S11 BT") No trace of second BT, but Cripple Horse Road has been constructed through its location. (Record: "From which a tamarack 28" in diameter bears S79° 10° W 69 links)

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: May 19,1966

DIAGRAM OF CORNER:

To perpetuate this corner we create two new reference monument trees, which bear from the center of the stone: A 10" Douglas-fir bears S42°E, 61 links, and a 12" ponderosa pine bears S22°W, 52 links distance; both bouble blazed and scribed RM. We piled rock around the original corner; We posted above corner rock with metal "monument sign"; put FS bearing tree posters on RM trees; we put a BLM bearing tree sign on the original 7" tamarack bearing tree; and we put up two new boundary signs on both ownership lines, one interior, and one between Sections 1 and 2.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal	We R. Christianson, V. Coble certify that the information shown herein is true and	
	certify that the information shown herein is true and correct.	N. TOIN ROTH
	Rad D. Clibian	1 4
	Signature of Ground Party Chief	ر ی او ی
	I, I. M. Tillotson Stanley J. Skousen	
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this	,
	fecordation form and approve the same.	= Corner recorded on the sheet
	Stenature of Surveyor	

I. M. Tillotson, E. Laven,

2532S

Registration Number

Office of Clerk and Recorder, County of JAMIN This "corner record" was filed for record on the assigned page No. 282 in book No..... County