INSTRUCTIONS

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- 3. Description of monument and accessories set to perpetuate the corner position.
 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sessed by Bestelesser.
- 6. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Sec. Cor. of S8,9,16,&17 T. 31N Lincoln P.M.M County

I. 1903 GLO Record: Set a slate stone 12x10x8 ins., 8 ins. in ground, marked with notches on S. and E. edges and blaze 4 bearing trees. 1976 BLM Remonumentation: The corner of sections 8,9,16, and 17, monumented with a slate stone 12x10x8 ins., firmly set 8 ins. in ground, marked with 4 notches on the S. and E. edges and witnessed by two original bearing trees:

Pine, 30 ins. diam., bears N. 541°E., 29 lks. dist., mkd. T31N R29W S9 BT.

Larch, 16 ins. diam., bears S. $31\frac{1}{2}$ °E., 35 lks. dist., with a healed face. (Record=S. 52 3/4°E.)

At the corner point,

Set an iron post, 30 ins. long, 2 1/2 inch diam.,

24 ins. in ground with brass cap marked:

From which new bearing trees:

Fir, 6 ins. diam., bears S. 52 % W. 17 1ks. dist., mkd. T31N R29W S17 BT.

Fir, 6 ins. diam., bears N. 14 3/4°W.,

53 lks. dist., mkd. T31N R29W S8 BT.

r31N R29W 8 8 S 9 S 17 | S 16 1976

I found a BLM monument, protruding 8 ins. above ground, with a brass II. cap marked as described in the BLM records, from which the following references:


Larch, 18 ins. diam., bears S. 28°E., 22.9 ft. (34.7 lks.) dist., with a healed face.


Pine, 23 ins. diam., bears N. 53°E., 19.7 ft. (29.8 1ks.) dist., scribing not visible.

Fir, 5 ins. diam., bears N. 15°W., 35.1 ft. (53.2 lks.) dist., with a healed face.

Fir, 7 ins. diam., bears S. 54°W., 11.6 ft. (17.6 lks.) dist., with a healed face.

III. Set a Carsonite guard post with "Survey Marker" decal attached, 1 ft. N. of corner. Painted a red band around each bearing tree and attached an "Attention" and "Bearing Tree" signs where needed.





SKETCH OF CORNER	Employer: U.S. Forest Service
Office of Clerk and Recorder, County of Jincoh	. This "corner Sec. 8
record" was filed for record on the	day of 19 85
was noted on the cross-index plat and is assigned page No.	2980
book No Janet St Suga	fly Sel Sixe foff
Coun	the Official Deputy
Cross Index No. J-9	31N , 29W

CORNER this sheet



I. ORIGINAL AND/OR SUBSEQUENT RECORD:

This item should describe or quote those portions of the original or subsequent record which were used in evaluating the corner position. The original record will usually be the General Land Office field notes. Subsequent record can come from several sources: Previously filed corner records, maps and plats, private and public records, etc. Some of the subsequent record, even though not in the public record, but known to have validity by the surveyor, may be quoted and appropriately noted.

The record data helps support the reestablished corner position because it clearly shows what history the surveyor based his corner position on. In some cases, however, the record may be unknown or not pertinent. A statement to that effect should appear on the corner record.

11. DESCRIPTION OF EVIDENCE FOUND OR METHOD OF LOCATING CORNER POSITION:

This item will describe the original or subsequent record evidence found. If portions of the found evidence cannot be recordled with the record, then the disregarded record should be noted, and, if possible, an opinion as to its cause narrated.

If no physical evidence of the original or subsequent monuments and accessories can be found, then the method used to reestablish the lost or obliterated corner (single proportion, fence intersection, parol evidence, terrain calls, centerline of road, etc.) shall be indicated.

III. DESCRIPTION OF MONUMENTS AND ACCESSORIES SET TO PERPETUATE THE CORNER POSITION:

This Item should list all details about the corner and its location which will help exclusively identify the corner position; including size and type of monument, how marked if not shown in sketch, and distinguishing topographic calls which help locate the corner. In many cases, instructions on how to find the corner should be included.

References or ties to other corners are optional and may be drawn on the face or back of the corner record form, or references to Certificate of Survey may be made. Separate drawings may be attached to the corner form.

If state plane coordinate values for the corner position are shown, then the control upon which they are based should be indicated.

IV. SKETCH OF CORNER:

This item will usually show how a found or set corner is marked and may also show topography or accessory monuments found or set and their relation to the corner. There is no stipulated format; the sketch could be transcribed field note entries.

V. CERTIFICATION:

The name and signature of the ground party chief is optional.

The Surveyor who performed or directed the field work which is depicted on the "Certified Corner Record" shall sign and affix his seal in the Certification.

The employer blank is optional but useful in tracking down original field note data or adjacent record if, in the future, questions arise about the corner.

vi

The Cross Index at the bottom of the page should be completed by the Surveyor. Only the single Township Index where the corner is filed shall be completed.

The lower righthand corner is a corner location diagram and should have the pertinent section filled in at the top and a closed circle indicating the appropriate corner position in the section filled in. This is intended to be an aid in searching the "Record" once it has been filed.

