

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 27 26
34 35 T. 31N R. 29W P.M.M. Lincoln County

RECORD

ORIGINAL SURVEY - GEORGE FESSENDEN - 1903

....Set a sandstone 15X12X8 inches, 10 inches in the ground for the corner of Sections 26, 27, 34, and 35, marked with 1 notch on the S. and 2 notches on the E. edges, from which:

- A 6" pine bears N24E, 42 links, marked "T31N R29W S26 BT"
 A 3" pine bears S84E, 70 links, marked "T31N R29W S35 BT"
 A 20" pine bears S28W, 70 links, marked "T31N R29W S34 BT"
 A 5" pine bears N44 1/2W, 65 links, marked "T31N R29W S27 BT"

1972 BLM REMONUMENTATION

....Found the original stone and 2 original bearing trees:

- A 9" pine bears N24E, 42 links, marked "T31N R29W S26 BT"
 A 9" pine bears N44 1/2W, 65 links, marked "T31N R29W S27 BT"

....Set a 30" X 2.5" iron pipe, 24 inches in the ground with a brass cap marked T31N R29W from which:

S27 S26

S34 S35

1972

- A 12" fir bears S63 1/4W, 61 links, marked "T31N R29W S34 BT"

FOUND


Found the 1972 BLM brass cap marked as shown above and bent over to the north. The bearing trees were still alive and 15", 12" and 16" respectively.

PERPETUATION

I uprighted the monument and repositioned it at record distance from the existing bearing trees and scribed a new bearing tree in Section 35:

- A 16" Ponderosa Pine bears S4E, 137.6 ft. marked T31N R29W S35 BT.

Bearing tree tags were attached to all of the trees with Land Monument Signs attached to the back. All trees were painted with a 6" band and the blazes were painted red. Placed a 6' metal post with Land Survey Marker decal 6' north of the corner.




James R. Staples
 I, James R. Staples, certify the information shown herein is true and correct.
 Signature of Party Chief
 James R. Staples
 I, James R. Staples, certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act," 20-2-201, M.C.A.
 Signature of Surveyor & Seal
 Date: 1-23-92 Reg. No. 9958
 Employer: J.R.S. & Associates

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Jan 24, 1992 was noted on the cross-index plat and is assigned page No. 4660, in book No. _____

Coral M. Cummings by Dee Buckhoff
 County Official

Cross Index No. V17 T. 31N R. 29W P.M.M.

Sec. 27



• - corner this sheet

INSTRUCTIONS TO SURVEYORS FOR COMPLETION OF CERTIFIED CORNER RECORDATION FORMS

I. ORIGINAL AND/OR SUBSEQUENT RECORD:

This item should describe or quote those portions of the original or subsequent record which were used in evaluating the corner position. The original record will usually be the General Land Office field notes. Subsequent record can come from several sources: Previously filed corner records, maps and plats, private and public records, etc. Some of the subsequent record, even though not in the public record, but known to have validity by the surveyor, may be quoted and appropriately noted.

The record data helps support the reestablished corner position because it clearly shows what history the surveyor based his corner position on. In some cases, however, the record may be unknown or not pertinent. A statement to that effect should appear on the corner record.

II. DESCRIPTION OF EVIDENCE FOUND OR METHOD OF LOCATING CORNER POSITION:

This item will describe the original or subsequent record evidence found. If portions of the found evidence cannot be reconciled with the record, then the disregarded record should be noted, and, if possible, an opinion as to its cause narrated.

If no physical evidence of the original or subsequent monuments and accessories can be found, then the method used to reestablish the lost or obliterated corner (single proportion, fence intersection, parol evidence, terrain calls, centerline of road, etc.) shall be indicated.

III. DESCRIPTION OF MONUMENTS AND ACCESSORIES SET TO PERPETUATE THE CORNER POSITION:

This item should list all details about the corner and its location which will help exclusively identify the corner position; including size and type of monument, how marked if not shown in sketch, and distinguishing topographic calls which help locate the corner. In many cases, instructions on how to find the corner should be included.

References or ties to other corners are optional and may be drawn on the face or back of the corner record form, or references to Certificate of Survey may be made. Separate drawings may be attached to the corner form.

If state plane coordinate values for the corner position are shown, then the control upon which they are based should be indicated.

IV. SKETCH OF CORNER:

This item will usually show how a found or set corner is marked and may also show topography or accessory monuments found or set and their relation to the corner. There is no stipulated format; the sketch could be transcribed field note entries.

V. CERTIFICATION:

The name and signature of the ground party chief is optional.

The Surveyor who performed or directed the field work which is depicted on the "Certified Corner Record" shall sign and affix his seal in the Certification.

The employer blank is optional but useful in tracking down original field note data or adjacent record if, in the future, questions arise about the corner.

VI.

The Cross Index at the bottom of the page should be completed by the Surveyor. Only the single Township Index where the corner is filed shall be completed.

The lower righthand corner is a corner location diagram and should have the pertinent section filled in at the top and a closed circle indicating the appropriate corner position in the section filled in. This is intended to be an aid in searching the "Record" once it has been filed.

NOTED 1989