

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner C $\frac{1}{4}$ Cor. Sec. 33 T. 31N R. 30W P.M.M. Lincoln County

No original corner set by GLO.

Set a $\frac{3}{4}$ " USFS driveable monument 30" long, 21" deep w/ $\frac{3}{4}$ " alum. cap
mkd: T31N R30W Corner fall on N'ly slope approx. 300 feet N. of
C $\frac{1}{4}$ S33 ridge.


1987

3976ES

Bearing trees: A 21" fir bears S56°E 16.7 feet, mkd. C $\frac{1}{4}$ S33 BT.
A 13" pine bears S75°W 15.3 feet, mkd. C $\frac{1}{4}$ S33 BT.
Decl. 20°E (assumed)

Built a rock cairn 3' diam. around monument and cleared to 6' diam.
Set a sign post near mon. Painted and signed all bearing trees as per
USFS Specs.

Cor. Mkd: T31N R30W
C $\frac{1}{4}$ S33
1987
3976ES



CERTIFICATION

1. Robert E. Findorff

certify the information shown herein is true and correct.

Signature Ground Party Chief

1. Robert E. Findorff

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (M.C.A. 82-2-201, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 11/11/87 Reg. No. 3976ES


Employer: Self

SKETCH OF CORNER (SEE ABOVE)

Office of Clerk and Recorder, County of Lincoln. This "corner
record" was filed for record on Nov 16, 1987
was noted on the cross-index plat and is assigned page No. 3700, in
book No. _____

Grant B. Sugar by David Smith
County Official Deputy

Sec. 33, T31N, R30W



• - corner this sheet

Cross Index No. X-11 T. 31N R. 30W P.M.M.

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors