

**CERTIFIED LAND CORNER RECORDATION**

Cadastral Retracement  $\frac{1}{4}$  cor. 31/32 T31N R30W Montana Principal Meridian

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T31N R30W Montana Principal Meridian G.L.O. notes book 8942 page 44 has an iron post 30" long,  $2\frac{1}{2}$ " in diameter, 27" in the ground with a brass cap marked:

Found the brass cap undisturbed and in good condition.

T31N R30W  
S31 | S32  
1964

Record: 8" fir bearing N22° E, 54 lks., marked  $\frac{1}{4}$  S32 BT  
Found: Bearing tree alive and still growing and presently 12" in diameter

Record: 6" fir bearing N43° W, 36 lks., marked  $\frac{1}{4}$  S31 BT  
Found: Bearing tree alive and still growing and presently 11" in diameter

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

4/15/74

Date of work:.....

No added monumentation.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Sketch on reverse side

Surveyor's Seal



I, James R. Staples certify that the information shown herein is true and correct.


*James R. Staples*  
Signature of Ground Party Chief

I, JOHN C. ERICKSON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*John C. Erickson*  
Signature of Surveyor

3979 S  
Registration Number

DIAGRAM OF CORNER:



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 28 day of Mar 1989, was noted on the cross-index plat and is assigned page No. 4000, in book No. ....

*Janet B. Sugley*  
County Official

11" FIR BEARING N43°W,  
36 LKS. MARKED  
1/4 S31 BT



31

12" FIR BEARING N22°E,  
54 LKS MARKED 1/4 S32 BT



32

BLM BRASS CAP MKKD.

73IN R30W

1/4

S31

S32

1964

