## CERTIFIED LAND CORNER RECORDATION

Cadastral Retracement 1 cor. 30/29 T31N R30W Montana Principal Meridian

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T31N R30W Montana Principal Meridian G.L.Ol notes book8942 page 47 has an iron post 30" long 2½" in diameter 27" in the ground marked T31N R30W

Found the brass cap undisturged and in good condition.

Record: 16" dead pine bearing S84½ E, 36 lks., marked  $\frac{1}{4}$  S BT Found: Bearing tree still in tact

Record: 6" fir bearing N39°E, 15 lks., marked \( \frac{1}{4} \) S29 BT Found: Bearing tree alive and still growing and presently 8" in diameter

Record: 9" fir bearing N33°W, 30 lks., marked 1 S30 BT

Found: Bearing tree alive and still growing and presently 14" in diameter DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/12/74....

No added monumentation

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Sketch on reverse side

MINTER NT A JOHN C. **ERICKSON** 3979 S SURVEY

Surveyor's Seal

correct.

Signature of Ground Party Chief

JOHN C. ERICKSON

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> Crubo Signature of Surveyor

> > 3979S Registration Number

DIAGRAM OF CORNER:

= Corner recorded on the sheet

Office of Clerk and Recorder, County of ....

This "corner record" was filed for record on the and day of

19...... was noted on the cross-index plat and is

4002, in book No.....

Form 125-3690

assigned page No...

14"FIR BEARING N33°W , 30 LKS. MARKEO - 14 530 BT



8" FR BEARING N39°E,
15 LKS., MARKED
1/4 529 BT

30

29

Bum Beass cap MEXO. T3IN R3OW /4 S30 S29 15" DEAD PINE BEARING 5841/2°E, 36 LKS., MEXO. 1/45 -- BT