CERTIFIED LAND CORNER RECORDATION

T31m R30W	DESCRIPTION OF	CORNER EVIDE	NCE FOUND, AND	original record notes book 89	(IF KNOWN) 42 pages 45	and 46
has a 30"	iron post,	2½" in diam	neter, 27" in	n the ground w	ith a brass	cáp
marked	T31N S29	Found brass	s cap in good	l condition and	d undisturbe	d.
	S32	•	•			

R30W 1964

Record: 10" fir bearing S50°W, 6 1ks., marked T31N R30W X2X BT Found: Bearing tree alive and still growing and presently 15" in diameter

Record: 8" fir bearing N84°W, 27 lks., marked T31N R30W S29 BT Found: Bearing tree alive and still growing and presently 13" in diameter

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Mey 14

No added monumentation...

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side.....

Surveyor's Seal

JOHN C. ERICKSON 3979 S SURVE James R. Staples

certify that the information shown herein is true and correct.

Signature of Ground Party Chief

JOHN C. ERICKSON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this KOOTENAI recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

RIVER


= Corner recorded on the sheet

39795

Registration Number

Office of Clerk and Recorder, County of This "corner record" was filed for record on the 25 day of Max 1989, was noted on the cross-index plat and is assigned page No. 4017, in book No. T 3/N R 30 W Cross Index No..... Form 125-3690

W(



13" FIR BEARING N84°W
27. LOW MEXO. TSINR30W 529 MC BT

BEARING 550°W MEND T3IN R3OW 532 MC BT