CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T31N R30W Montana Principal Meridian G.L.O. notes book 3422 page 26 has a "boulder "20x10x10 15" in the ground with two bearing trees. Found 3/4" re-bar and one bearing tree.

Record: 14" cedar bearing N27-40'W, 9 lks., marked T31N R30W S30 MC BT Found: 20" cedar bearing north, 9 lks., marked with same scribe.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work June '74

No added monumentation

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side.....

	•	DIAGRAM OF CORNER:
Surveyor's Seal	I,	N.
MAN NTAN	Signature of Ground Party Chief JOHN C. ERICKSON	KOOTENAL M.C. RIVER >
JOHN C. ERICKSON ************************************	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	7
3979 S SURVE	Signature of Surveyor	= Corner recorded on the sheet
	Registration Number	

Office of Clerk and Recorder, County of Lincoln This "corner record" was filed for record on the 28 day of Mor 19....., was noted on the cross-index plat and is 4020 in book No..... assigned page No.... Cross Index No. T. 31N R. 30W Mer. Form 125-3690

RO" CEDAR BEARING NORTH MRKO T3IN R3OW S30 MC BT 30 3/4" REBAR