CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) T31N R30W Montana Principal Meridian G.L.O. notes back 8942 page 196 has 30" iron post, 2½" in diameter, 26" in the ground with a brass cap marked: T31N R31W

S33 Found the brass cap undisturbed and in good condition. T3**0**N

Record: 26" fir bearing $S4^{19}_{2}E$, 84 lks., marked $\frac{1}{4}$ S4 BT

Found: Bearing tree alive and still growing and presently 28" in

diameter

Record: 8^{m} fir bearing N46°W, 29 lks., marked $\frac{1}{4}$ S33 BT

Bearing tree alive and still growing and presently 12" diameter

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/22/74

No added monumentation


SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Sketch on reverse side

Form 125-3690

DIAGRAM OF CORNER: I, James R. Staples Surveyor's Seal T3IN RBOW certify that the information shown herein is true and correct. ATA CHARLES Stapled Signature of Ground Party Chief JOHN C. ERICKSON certify that I have carefully performed or reviewed the JOHN C work done on the diagrammed corner as reported on this T30N ERICKSON recordation form and approve the same. SURVE MINIMINI 3979 S = Corner recorded on the sheet Line Signature of Surveyor 39795 Registration Number

Office of Clerk and Recorder, County of ... This "corner record" was filed for record on the 28 day of ______ .. 19.57, was noted on the cross-index plat and is assigned page No. 404/, in book No..... Cross Index No. ZII T. 31N R.



BLM BRASS CAP MARKED: 4 T3/N R30W

1/4 <u>533</u> 54 T30N 1965

28" FIR BEARING SA1/2°E, 84 LKS., MARKED 1/4 S 4 BT