


CERTIFIED CORNER RECORDATION

Corner MS 10965 COR. 2 Sec. 24 T. 31N R. 30W P.M., MT. Lincoln County
CPD NO. 3 LODE

- I. 1976 Original B. L. M. survey by Arthur C. Rader: Cor. No. 2, identical with Cor. no. 3 of the CPD No. 4 lode of this survey. Set an iron post, 30 ins. long, 1 in. diam., 24 ins. in the ground, with brass cap mkd. 2CPD3-3CPD4-10965; from which:
- A pine, 8 ins. diam., bears N 45° E, 9.0 ft. dist. mkd. 3CPD4-10965 BT.
A pine, 8 ins. diam., bears N 66°30' W, 24.5 ft. dist., mkd. 2CPD3-10965 BT.
A cor. of the location bears N 46° 10'E, 75.5 ft. dist.
- II. Found a 1 1/2 in. diam. iron pipe, 16 ins. above ground, firmly set, with a 3 in. diam. brass cap, mkd. as shown:.




from which:

- A pine, 7 ins. diam., bears N 65°E, 9.0 ft. dist., mkd. 3 CPD 4-10965. (Rec: N 45°E.)
A pine snag, 7 ins. diam., bears S 75°W, 24.5 ft. dist., mkd. 2 CPD 3-10965. (Rec: N 66° 30' W)
A steel guard post with a property boundary decal attached. 0.4 ft. dist.


- III. Established one new bearing tree:
A pine, 7 ins. diam., bears S 23°E, 11.2 ft. dist., mkd. "X" BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East.



SKETCH OF CORNER



I, Jeff Hintz
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Ronald A. Pearson
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-001, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 1/10/96

Reg. No.: 9008LS

Employer U.S. FOREST SERVICE

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on 2-28-96 was noted on the cross-index plat and is assigned page No. 8221, in book No. Coral M. Cumming By DB
County Official

