
## **CERTIFIED CORNER RECORDATION**

Corner MS 10965 COR. 2 Sec. 14 T. 31N R. 30W P.M., MT. Lincoln County CPD NO. 17 LODE

I. 1976 Original B. L. M. survey by Arthur C. Rader: Cor. No. 2. Set an iron post, 30 ins. long, 1 in. diam., 24 ins. in the ground, with brass cap mkd. 2CP17-10965; from which:

A larch, 14ins. diam., bears S 70°20' W, 21.4 ft. dist. mkd. 2CPD17-10965 BT. A fir, 20 ins. diam., bears S 16°30' E, 17.7 ft. dist., mkd. 2CPD17-10965 BT. A cor. of the location bears East, 1.0 ft. dist.

II. Found a 1 1/2 in. diam. iron pipe, 13 ins. above ground, firmly set in a collar of stone, with a 3 in. diam. brass cap, mkd. as shown:



from which:

A fir, 20 ins. diam., bears S 16°E, 17.7 ft. dist., mkd. with visible scribe marks.

A larch, 14 ins. diam., bears S 70°W, 29.7 ft. dist., mkd. with visible scribe marks. (Rec: 24.1 ft.)

A steel guard post bears NORTH, 1.1 ft. dist., with Property Boundary decal attached.

A steel guard post bears WEST, 1.9 ft. dist., with Property Boundary decal attached.

III. Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East.

