

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found 1 1/2" iron pipe per C.S. No. 872
No original G.L.O. Record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Date of work: 4/20/81

I set a 5/8" X 24" rebar with a plastic cap stamped MDL 4232-S
From which: a 15" diameter ponderosa pine bears N72°W 23.2 feet
and a 21" diameter Ponderosa Pine bears S82°E 14.9 feet to center
of trees. and from which a 1 1/2" diameter pipe bears S85°36'05"W
4.17 feet.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE

Surveyor's Seal



I, L. A. Dolezal
certify that the information shown herein is true and correct.


L. A. Dolezal
Signature of Ground Party Chief

I, Melvin D. Lauteren
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Melvin D. Lauteren
Signature of Surveyor

4232-S
Registration Number

DIAGRAM OF CORNER:



● = Corner recorded on the sheet
CW 1/16th corner
Section 34, T31N,
R31W, P.M.,M.

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 22nd day of June 1981, was noted on the cross-index plat and is assigned page No. 1036, in book No. 1

Eleonore L. Vaughn, by Betty Bell,
County Official Deputy

NW 1/4 COR.
FD. ALUMINUM MONUMENT
USFS. 1980
2 B.T.'S

1317.10' FB.
1317.45' FB. C.S. 872
S 1° 09' 09" W
S 1° 09' 09" W

BT.
20" P. PINE
N 72° W
23.2'

0° 36' 05" W
4.17'
FD. 1 1/2" FIRE

CW 1/4 COR.
Set 5/6 REAR 4232-S

S 82° E
14.9'
BT.
21" P. PINE