

**CERTIFIED LAND CORNER RECORDATION**  
(REFERENCE FSM 7153.53)

**DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)**

Found BIM brass cap firmly set (record, set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked)  
From which

A fir, 20 ins. diam., bears N. 60° E., 100 lks. dist., visible marks B.T. (Record)

A fir, 20 ins. diam., bears S. 4° E., 82 lks. dist., mkd. ¼ S. 15 B.T. (Record)

These two B.T.'s will be destroyed by reconstruction of the Pipe Creek Road #68.

T. 31N., R. 31W.  
¼ S 10  
S 15  
1962

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

Date of work: 4-2-70

New B.T.'s:

A 6 in. lodgepole pine bears N. 12½° E. - 19 links dist., Mkd. RM.

A 6 in. larch bears S. 4° W. - 22 links dist., Mkd. RM

Placed new bearing tree and attention signs at corner and painted iron post and rock mound.

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)**

(Record from 1962 B.L.M. field notes)

Surveyor's Seal

I, A. R. Trenkle  
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, Stanley J. Skousen  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen  
Signature of Surveyor

**DIAGRAM OF CORNER:**  
T. 31N., R. 31W.

N. ¼ S 10  
S 15

o = Corner recorded on the sheet

2532 S  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th. day of April 1970, was noted on the cross-index plat and is assigned page No. 178, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson  
County Official Deputy.

Cross Index No. J-15 T. 31 R. 31 Mer.