EAST_

CERTIFIED LAND CORNER RECORDATION

Cadastral Retracement cor. Section 25 T31N R31W Montana Principal Meridian

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

T31N R31W Montana Principal Meridian G.L.O. notes book 8942 page 56 has an iron post 30" long, $2\frac{1}{2}$ " in diameter, and 26" in the ground with a brass cap T31N marked

1₂525

Found brass cap underground in the fill of a power line road.

Record: 10" pine bearing S58 \mathring{W} , 39 lks., marked $\frac{1}{4}$ S25 BT Found: 12" pine stump bearing and distance good and marked $\frac{1}{4}$ S25 BT

Recard: 10" pine bearing N50W, 141 lks., marked 1/4 S.. BT

Did not have the recordation on this bearing tree since the notes were on 2

pages and they only sent us one.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/10/74

No added monumentation.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Sketch on reverse side

Surveyor's Seal

ANT A STATE JOHN C. **ERICKSON** 3979 S SURVEYONI

James R. Staples certify that the information shown herein is true and correct.

Staples amed. Signature of Ground Party Chief

JOHN C. ERICKSON

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

39795 Registration Number DIAGRAM OF CORNER:

TSM R3IN

= Corner recorded on the sheet

Office of Clerk and Recorder, County of ...

assigned page No. 4003, in book No.

This "corner record" was filed for record on the 25 day of Man

noted on the cross-index plat and is

T. 31N 125

Form 125-3690

R30W

10" PINE 141 LKS.,

10" PINE BEARING NSDOW 141 LKS:, UISIBLE SCRIBE: 14.5 - BT

25

30

12" PINE STUMP BERRING SS9°W, 39 LKS. SCRIBE: 44 525 BT BLM BEOSS COP Marked T31N

1/4 525

R31W