INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.
- Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

of Secs. 9, 10, 15 & 16 31 N., Lincoln Corner County 1901 G.L.O. record by Abram E. Jaqueth: Set a stone monument and marked four bearing trees. 1962 B.L.M. remonumentation record by Gerald F. Pittman et al: "The cor. of secs. 9,10,15 and 16, monumented with a argillite stone, 14x6x6 ins., firmly set and mkd. with 3 grooves on the E. and 4 grooves on the S. faces, and witnessed by the remains of the original bearing trees. At corner point; set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T31N R31W \$9 | \$10 \$16 | \$15 From which: 1963 The remains of the original bearing trees: A stump, 16 ins. diam., bears N70 E, 75 lks. dist., visible marks T31N R31W S10 (Record). A stump, 22 ins. diam., bears S64 1/2 E, 43 lks. dist., visible marks T31N R31W S15 BT. (Record: \$63 35'E, 43 1ks.) A decayed stump, bears S85 $^{'}$ W, 18 lks. dist., no marks visible. (Record) A stump, 20 ins. diam., bears N70 1/2 $^{'}$ W, 71 lks. dist., visible marks T31 R31W S9. (Record: N69 10'W, 71 1ks.' The new bearing trees: A pine, 8 ins. diam., bears $N29^{\circ}E$, 37 lks. dist., mkd. T31N R31W S10 BT. A pine, 8 ins. diam., bears $S60^{\circ}1/2^{\circ}E$., 33 lks. dist., mkd. T31N R31W S15 BT. A pine, 8 ins. diam., bears $$20^{\circ}W$, 64 lks. dist., mkd. T31N R31W S16 BT. A pine, 8 ins. diam., bears N42 $1/4^{\circ}$ W, 20 lks. dist., mkd. T31N R31W S9 BT. Bury the original stone alongside of the iron post." Found a 2 1/2 ins. diam. iron pipe, 4 ins. out of ground with 3 1/4 ins. diam. B.L.M. brass cap, marked as shown above, from which: A pine snag, 12 ins. diam., bears N30°E, 24.3 ft. (37 lks.) dist., mkd. T31N R31W S10 BT. A fallen pine, 11 ins. diam., bears S60°E, 21.8 ft. (33 lks.) dist., mkd. T31N R31W S15 BT. A fallen pine, 8 ins. diam., bears \$20 $^{\circ}$ W, 42.2 ft. (64 lks.) dist., mkd. T31N R31W \$16 BT. A pine snag, 9 ins. diam., bears N41 W, 13.2 ft. (20 lks.) dist., mkd. T31N R31W S9 BT. A stump, 18 ins. diam., bears $N69^{\circ}E$, 50.1 ft. (76 lks.) dist., mkd. T31N R31W S10. A stump, 23 ins. diam., bears $S62^{\circ}E$, 28.7 ft. (44 lks.) dist., mkd. T31N R31W S15 B. A fir, 18 ins. diam., bears 553 W., 29.1 ft. (44 lks.) dist., mkd. T31N R31W 816 BT. A stump hole, bears $886^{\circ}W$, 11.6 ft. (18 lks.) dist. A stump, 28 ins. diam., bears N70 $^{\circ}$ W, 47.0 ft. (71 lks.) dist., mkd. 31W S. Two 6 ft. galvanized steel guars posts with Land Survey Marker decal, East, 3 ft. & Property Boundary decal, North, 2 ft. III. Established three new bearing trees: A fir, 12 ins. diam., bears N58 E, 41.7 ft. dist., mkd. T31N R31W S10 BT. A fir, 12 ins. diam., bears S78 E, 39.6 ft. dist., mkd. T31N R31W S15 BT. A fir, 10 ins. diam., bears N65 W, 32.0 ft. dist., mkd. T31N R31W S9 BT. Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs. Magnetic Declination: 20 East MOH TAN CERTIFICA PON'ALD A PEARSON A Peder Raymond I. ______certify the information show Pearson certify that this Corner Record correctly represents work performed nder my direction in compliance Act" (70-22-18), et seq., M. (A.) (2) 1 23* 9/1/92 Reg. No. 9008LS FALLEN PINE U.S. FOREST SERVICE **SKETCH OF CORNER** Sec Office of Clerk and Recorder, County of . This "corner record" was filed for record on ... was noted on the cross-index plat and is assigned page No.

Cross Index No.

County Official

corner this sheet

book No. _