CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

CN 1/16 th.: No original record.

NE 1/16 th.: No original record.

CE 1/16 th.: Found squared 8" pine from which B.T., .8" diam.

CE 1/16 th.: Found squared 8" pine from which B.T., .8" diam. L.P. Pine bears S11°05'E 15.8 feet and B.T., 1.0' diam. P. Pine bears N86°51'W 49.04 feet. RECORD CALLS FOR: A squared pine for the corner from which a 12" pine bears S87 E 15.8' scribed and posted and a 12" pine bears N04 W 18.0' scribed and posted.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 5/26/79

CN 1/16 th.: Iset a 5/8"X24" rebar tagged GEB 4974—S from which a 0.9 diam. L.P. Pine bears N77°45'E 54.3 feet and a 1.0 diam. L.P. Pine bears SO1°00'W 7.9 feet, scribed and posted.

SEE REVERSE


SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE

Surveyor's Seal	I, ERACD E. BUNTON certify that the information shown herein is true and	
MTANTE CONTRACTOR	Signature of Ground Party Chief	
GERALD E. BUNTON 4974S PEGISTERED OSURVENININININININININININININININININININI	I, ERAD E, BUNTON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	1
	Signature of Surveyor 4974-S Registration Number	

DIAGRAM OF CORNER:



• = Corner recorded on the sheet CN 1/16, NE 1/16, CE 1/16 corners of section 33, T3lN, R3lW, P.M.M.

Office of Clerk and Recorder, County of Lineals)
Office of Clerk and Recorder, County of	
This "corner record" was filed for record on the ZAA. day of	Octaber 1979., was noted on the cross-index plat and is
assigned page No. 557, in book No.	Cheaner J. Taughan, by betty bell,
3 Form 125—7887	Cross Index No. X 12 T. 31 R. 31 Mer.

NE 1/16 th.: I set a 5/8"X24" rebar tagged GEB 4974-S from which a 1.0' diam. D. Fir bears S26°E 12.5 feet and a 1.1' diam. D. Fir bears .N29°21E 11.2 feet, scribed and posted.

CE 1/16 th. : I set a 5/8"X24" rebar tagged GEB 4974—S from which a found B.T., a 0.8' diam. L.P. Pine bears S26 E 21.9 feet and a found B.T., a 1.0' diam. P. Pine bears S76°W 13.0 feet and the squared 8" pine, reported to be the 1/16 th. corner in corner record book 1 page 206, bears S50°58'E 7.7 feet. Ipost new tags on the old B.T.'S.

3642.24' 139.45' 1321