

INSTRUCTIONS

- . Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Cor. No. 6 HES 751 T. 31 North R. 32 West P.M.M. Lincoln County

ORIGINAL - Harold Townsend - 1918 HES 751

Set a small stone marked with a cross "X" under an iron post, 2" diameter, 36" long, 24" in the ground with a brass cap marked 1918 6 HES 751 and a point on top from which:

A cross "X" on a Yellow Pine tree, 8" diameter, bears S72°24'E, 69 links (45.54') distant.

A cross "X" on a fir

tree, 10" diameter, bears S55°46'W, 70 links (46.20') distant.

Each blazed and scribed 6 HES 751 BT.

Raise a mound of stone 4' base, 2' high, south of comer.

FOUND:

Found 2½" brass cap marked as shown below on 2" diameter pipe.

A 17" diameter Douglas Fir with blaze and visible scribing and a BLM BT tag bears S56°W, 45.84 feet distant to aluminum nail in side center of tree.

A 24" Douglas Fir with healed blaze bears N8½°E, 10.33 feet distant to aluminum nail in side center of tree. Paint bearing trees with red paint and attach bearing tree tags.



24" DOUGLAS FIR FOUND 2½" BRASS CAP ON 2" PIPE 17" DOUGLAS FIR

CERTIFICATION

I, <u>James R. Staples</u>
Certify the information shown herein is true and correct.

Jame R. Ther

Signature Ground Party Chief

James R. Staples
 certify that this Corner Record correctly represents work performed by
me or under my direction in compliance with the "Corner Recordation

Signature of Surveyor & Scal

Act" (70-22-101, et seq., M.C.A.)

Date: 2/1/05 Reg. No. 9958 LS

Employer: J.R.S. Surveying, Inc.

SKETCH OF CORNER

Office of Clerk and Recor	This "corner 185535 BOOK: CCR CCER'S PAGE: 10799 Pages: 1
record" was filed for reco	and a second seco
was noted on the cross-in	RECORDED: 06/28/2005 10:25 KOI: CCGR'S CORAL M. CUMMINGS CLERK AND RECORDER
book no.	TO: FILED , County Official

Cross Index No. T. 31N R. 32W PMM

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

13 CORH 4

• - Corner this sheet