

INSTRUCTIONS

1. Original and/or substituted record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.


CERTIFIED CORNER RECORDATION

Corner 3 HES 935 T. 31 N R. 32 W P.M.M. Lincoln County

ORIGINAL USDA NOTES: USDA - Forest Service 1919

CORNER: 26 x 8 x 6 inch stone marked 3 HES 935 with "X" on top of stone
 "X" on Tamarack Tree, 16" dia. bears N.68°38'E., 114 lks distance
 "X" on Cedar Tree, 7" dia. bears N.88°09'W., 7 lks distance
 Each blazed and scribed MC 3 HES 935 BT

EVIDENCE FOUND: Found stone 26 x 8 x 6 inches laying on ground marked 3 HES 935, "X" on top of stone
 No witness marks found



26"x8"x6" stone

SKETCH OF CORNER

CERTIFICATION

I, _____
 certify the information shown herein is true and correct.

I, Robert C. Muster
 certify that this corner record correctly represents work performed
 by me or under my direct supervision in compliance with the "Corner
 Recordation Act" (70-22-011, M.C.L.A.)

Date: 11/30/82


Employer: PROFESSIONAL CONSULTANTS, INC.

Office of Clerk and Recorder, County of Lincoln. This "corner
 record" was filed for record on the January 21st day of 1982
 was noted on the cross-index plat and is assigned page No. 1498, in
 book No. 1

Eleanor L. Vaughn by Betty L. Conces
 County Official Deputy

Cross Index No. L.M-18, 19 T. 31N R. 32W P.M.M.

Sec. 14



• - corner this sheet